

Spray Types for Decorative Texture Coats on Wall Surfaces.

Powder/Chip of Marble, Granite, Natural Stone + Acrylic Resin for exterior/interior Wall. Excellent Color UV & High Performance of Fungus Resistance & Protection against Corrosion

Product Application: **Texture Stone Chip**, is high-viscosity paste form acrylic resin adhesive & combined of Powder/Chip of marble, granite, natural stone contains. Offers excellent color UV, high hardness, fungus resistance and protection against corrosion. The texture coats has applied on wall system for high rinse building, warehouses, garages, shopping centers, condominium, apartment & commercial etc.

Advantage & Properties: The specific advantage offered by solvent free coating & natural stones. Offers excellent color UV, high hardness, fungus resistance and protection against corrosion. Very good adhesion, the system recommended for cement wall, concrete can also be applied on other walls, mineral substrates, as stones, bricks, fibre-glass, metal surface or even tiles and glass.

Ultraviolet Resistance: **Not reflection to eye and no yellowing after 100 hours.**

- ❖ Adhesion is always good on mineral substrates surfacing.
- ❖ Very good mechanical properties following optimal cure.
- ❖ As elegant and durable as natural stone finish.
- ❖ Forms a hardness texture finish that is excellent of abrasion & scratch.
- ❖ Good in no dust from substrate coatings easy to clean, improved visibility.
- ❖ Excellent of fungus resistance, Good on hygienic wall surfacing.
- ❖ Adhesion promoting primers between old with new concrete.
- ❖ Non-toxic, the coatings have been cured applied on health floor.

Available of Color



Code: GS 23
Texture Stone Chip



Code: GS 27
Texture Stone Chip



Code: GS 33
Texture Stone Chip



Code: MS 51
Texture Stone Chip



Code: MS 53
Texture Stone Chip



Code: MS 55
Texture Stone Chip



Code: MS 57
Texture Stone Chip



Code: MS 59
Texture Stone Chip

Performance of Property Details

	Texture Stone Chip Granite Type	Texture Stone Chip Marble Type	Texture Stone Chip Natural Stone Type
Specific Gravity:	1.80-1.90gm/cm ³	1.70-1.85gm/cm ³	1.85-2.00gm/cm ³
Cure Time:	120-180 mins	120-180 mins	120-180 mins
Viscosity:	130000 cps [±5000]	125000 cps [±5000]	135000 cps [±5000]
Compressive Strength:	18.50N/mm ²	17.08N/mm ²	19.50N/mm ²
Elongation at Break:	2.50%	2.10%	2.50%

**Surface Preparation
& Method Application**

Surface to be repaired or sealed must be clean and sound. Concrete must be free of dust, sealers, grease and other bond inhibiting contaminants.

Concrete must cured at least 28 days and have with minimum Compressive Strength of 20 N/mm². Those cement slurry, plaster droppings, etc. must be remove, the surface of concrete free of oil, grease, and other loose particles and contaminations.

Texture Stone Chip, it's easy to applied, there for using texture gun for Spray Equipment, application must be made in two proceed, first layer of Primer Coat & second layer coat of Texture Stone Chip [finish coat], (**Refer to Coverage Chart**)

Optional, if require of UV 100% system, is must applied clear coat "Gem Top Guard" for protection layer.

Packing & Size:

5 kg, 10 kg, 20 kg or 25 kg pack

Coverage Chart:

1st layer

Primer Coats layer

3-5/m² per kg

2nd layer

Texture Stone Chip

4.50-6.00 kg/m²
depends on choice of powder/chip

Optional layer for UV 100%**Gem Top Guard**

3-4/m² per kg

Mixing:

Texture Stone Chip, Supplied as two-component system. Mix materials with low speed drill and paddle for approximately two [2] minutes. Insure a thorough mix. Never mix more material than can be used in thirty (30) minutes. Do not apply Acrylic when ambient or surface temperatures are below 50 °F

Storage

12 months from date of manufacture in original sealed container stored undercover 25 °C, at ambient temperature away from heat, and dry conditions. For clearing equipment, use special solvent liquid.

**LaMaCo System Sdn Bhd**

407, Jalan Perusahaan 6, Taman Bandar Baru Mergong, 05150 Alor Setar, Kedah, Malaysia

Tel : +60-4-771 1111

Fax : +60-4-772 4444

Http : www.lamaco.com

Email : info@lamaco.com

The General Term & Conditions

All recommendations for use of our product, whether given by us in writing, verbally, or to be implied from the results of tests carried out by us are based on the current state of our knowledge Notwithstanding any such recommendations the Buyer shall remain responsible for satisfying himself that the products as supplied by us are suitable for this intended process or purpose. Since we cannot control the application, use or processing of the products, we cannot accept responsibility therefor. The Buyer shall ensure that the intended use of the products will not infringe any third party's intellectual property rights. We warrant that our products are free from defects in accordance with and subject to our general conditions of supply.

The above mentioned details Specified key data are individually checked throughout, guarantee, and included in the certificates of Analysis (CoAs). & Typical key data are spot checked, the value are typical for the product and are indicated for information only. The values are not guaranteed or included in the CoAs.

Handling Precautions

Mandatory and recommended industrial hygiene procedures should be followed whenever our products are being handled and processed. For additional information please consult the corresponding product safety data sheets and the brochure "Hygienic Precautions for Handling Plastic Products"

IMPORTANT: While the information and data sheet contained in this promotional literature are presented in good faith and believed to be reliable, they do not constitute a part of our terms and conditions of sales unless specifically incorporated in our Order acknowledgement. Nothing herein shall be deemed to constitute a warranty, express or implied, that said information or data sheet are correct or that the products described are merchantable or fit for a particular purpose, or that said information, data sheet or products can be used without infringing patent of third parties.